

## **HEAVY DUTY COMPRESSION**

The X50 is designed for users, who demand a high quality machine with focus on reliability, superior press force, and a safe, functional working environment for the operator.

It has a large filling opening and a fast cycle time, making the daily operation as rational as possible.



Technical specifications	
Press force (t)	50
Power supply	3x400V 50Hz 32A
Motor (kW)	5.5
Noise level (dB)	71
Cycle time (sec)	23
Dimensions LxWxH (mm)	1950 x 1400 x 2580
Weight (kg)	2590
Filling opening WxH (mm)	1090 x 600
Filling height (mm)	1250
Chamber height (mm)	1710
Stroke (mm)	1210
Bale size WxDxH (mm)	1200 x 800 x 1100
Bale weight cardboard (kg)	400-450
Bale weight plastic (kg)	450-550











1 Compact your waste and eject the finished bale. 2 Remove and store the bale until collection. 3 The bale is ejected by a safe two-hand operation. 4 The cross cylinders ensure stable compression and a low overall height.

- Effective operation

  Due to a fast cycle time
- Easy installation With a low overall height
- Safe and steady opening of door Operated by a strong threaded spindle

Elkoplast CZ, s.r.o. Štefánikova 2664 760 01 Zlin Tel. +420 575 571 000 Fax +420 575 571 099 elkoplast@elkoplast.cz www.elkoplast.cz